CX520D

Coaxial Relay SPDT 3x N, 12VDC

Rating: Not Rated Yet
Price:
Sales price without tax: 104,96 €

Ask a question about this product

Description

Electrical Contact Specifications	
Contact Arrangement	SPDT
Operational Temperature	-25°C to +70°C
Contact Resistance (Max)	0.1Ω
Life Expectancy	
Mechanical	200,000 - 500,000
Electrical	100,000 - 200,000
Coil Specifications	
Coil Voltage	12 VDC (Other voltages available)
Electrical Characteristics	
Operating Voltage	10-15 VDC
Coil Resistance	1.5 Ω
Voltage Drop	0.1 VDC
Current	8 A
Power Consumption	1.5 W
Coil Current	8 A
Connectors	
Connector	N-Type
Impedance	50 Ω
Frequency Range	DC to 3 GHz - 12.5 GHz
Insertion Loss	0.3 dB (DC to 3 GHz) - 0.5 dB (12.5 GHz)
Isolation	60 dB (DC to 3 GHz) - 40 dB (12.5 GHz)

Frequency	Loss	Frequency	Loss	Frequency	Loss
DC	0.05	1	0.15	10	0.45
0.05	0.05	2	0.20	12.5	0.50
0.1	0.05	3	0.25	15	0.60
0.2	0.05	4	0.30	18	0.70
0.5	0.10	6	0.35	20	0.80
0.8	0.12	8	0.40	25	0.90